

SAFETY DATA SHEET

PART No. PG205T

1. IDENTIFICATION OF THE PRODUCT

PRODUCT NAME: BELT GUARD 12x500ML
COMPANY NAME: Autogem Motor Concepts LLP
Abbey Road
Park Royal
London
NW10 7SU
England
TEL: +44 (0)208 838 0910
FAX: +44 (0)208 838 1854

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT MODIFIED NAPHTA-NAPHTA (PETROLEUM) SOLVENT REFINED LIGHT 30-50%
EINECS: 265-086-6 CAS:64741-84-0
[F] R11; [Xi] R38; [N] R51/53; [Xn] R65 ; [-]R67
• BUTANE 10/30%
EINECS: 203-448-7 CAS: 106-97-8
[F+] R12

3. HAZARDS IDENTIFICATION

Main hazards: extremely flammable, irritating to skin, toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment, vapours may cause drowsiness and dizziness.

Other hazards: In use, may cause form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES

Skin contact: There may be irritation and redness at that site of contact.
Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of water.

Eye contact: There may be irritation and redness. The eyes may water profusely.
Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: There may be soreness and redness of the mouth and throat.
Wash out mouth with water. Consult a doctor.

Inhalation: There may be irritation of the throat with a felling of tightness in the chest. Exposure may cause coughing or wheezing.
Remove casualty from ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE FIGHTING MEASURES

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
- Exposure hazards:** In combustion emits toxic fumes.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct with the substance. Ensure there is sufficient ventilation of the area. Do not handle in confined space. Avoid the formation or spread of mists in the air.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Hazardous ingredients:** BUTANE
WEL (8 hr TWA): 1450 mg/m³ WEL (15 min STEL): 1810 mg/m³
- Engineering measures:** Ensure there is sufficient ventilation area. The floor of the storage room must be impermeable to prevent the escape of liquids.
- Respiratory protection:** Self-contained breathing apparatus must available in case of emergency.
- Hand protection:** Protective gloves.
- Eye protection:** Safety glasses. Ensure eye bath is to hand.
- Skin protection:** Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|--------------------------|----------------------|-----------------------------|--------------------------------|
| State: | Aerosol | Oxidising: | Non-oxidising (by EC criteria) |
| Colour: | Colourless | Solubility in water: | insoluble |
| Odour: | Characteristic odour | Flash point deg C: | -35 |
| Evaporation rate: | Fast | | |

10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions.
- Conditions to avoid:** Heat.
- Materials to avoid:** Strong oxidising agents. Strong acids.
- Haz. decomp. Products:** In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposures and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialized disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID:

UN no: 1950
Classification code: 5F
Shipping name: AEROSOL
Labelling: 2.1



IMDG / IMO:

UN no: 1950
Class: 2
EmS: F-D, S-U
Marine pollutant:
Labelling: 2.1

IATA / ICAO:

UN no: 1950
Class: 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
Irritant.
Dangerous for the environment.



Risk phrases:	<p>R12: Extremely flammable.</p> <p>R38: Irritating to skin.</p> <p>R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R67: Vapours may cause drowsiness and dizziness.</p>
Safety phrases:	<p>S16: Keep away from sources of ignition - No smoking.</p> <p>S23: Do not breathe spray.</p> <p>S38: In case of insufficient ventilation, wear suitable respiratory equipment.</p> <p>S51: Use only in well-ventilated areas.</p> <p>S61: Avoid release to the environment. Refer to special instructions / safety data sheets.</p>
Precautionary phrases:	<p>Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.</p>
Haz. ingredients (label):	<p>LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT REFINED LIGHT; HEPTANE.</p>
Note:	<p>The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.</p>

16. REGULATORY INFORMATION

Risk phrases used in s.3:	<p>R11: Highly flammable.</p> <p>R38: Irritating to skin.</p> <p>R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65: Harmful: may cause lung damage if swallowed.</p> <p>R67: Vapours may cause drowsiness and dizziness.</p> <p>R50/53: Very toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.</p> <p>R36: Irritating to eyes.</p> <p>R12: Extremely flammable.</p>
----------------------------------	---

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.