

# SAFETY DATA SHEET

## TRL106 – RIM SEALER 5Kg

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** TRL106– RIM SEALER 5kg  
**Company** Autogem Motor Concepts LLP  
 Unit 6 Space Business Park  
 Abbey Road  
 London  
 NW10 7SU  
 United Kingdom  
 sales@autogem.co.uk  
 www.AUTOGEM.CO.UK

**Tel** +44 (0) 20 8838 0910  
**Fax** +44 (0) 20 8838 1854

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)		14807-96-6				
C9-11 Alcohol Ethoxylate with 8MeO		68439-45-2				

### 3. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

### 4. FIRST AID MEASURES

**Inhalation** May cause irritation to mucous membranes. Move the exposed person to fresh air.  
**Eye contact** May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist  
**Skin contact** May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.  
**Ingestion** May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use extinguishing media appropriate to the surrounding fire conditions.  
**Special hazards** Burning produces irritating, toxic and obnoxious fumes.  
**Advice for fire fighters** Wear suitable respiratory equipment when necessary.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Ensure adequate ventilation of the working area.
<b>Environmental precautions</b>	Do not allow product to enter drains. Prevent further spillage if safe.
<b>Cleaning up</b>	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
<b>Storage</b>	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Limit Values

Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -

<b>Appropriate engineering controls</b>	Ensure adequate ventilation of the working area.
<b>Individual protection measures</b>	Wear protective clothing.
<b>Eye / face protection</b>	In case of splashing, wear: Approved safety goggles.
<b>Skin / Hand protection</b>	Chemical resistant gloves (PVC).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>State</b>	Paste
<b>Colour</b>	Brown
<b>Odour</b>	Characteristic
<b>Water solubility</b>	Insoluble in water.

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable under normal conditions.
---------------------------	---------------------------------

## 11. TOXICOLOGICAL INFORMATION

No known adverse health effects.

## 12. ECOLOGICAL INFORMATION

No known adverse environmental effects.

## 13. DISPOSAL CONSIDERATIONS

Dispose of in compliance with all local and national regulations.

## 14. TRANSPORT INFORMATION

The product is not classified as dangerous for carriage

## 15. REGULATORY INFORMATION

Risk phrases No Significant Hazard.

## 16. OTHER INFORMATION

### **Text of risk phrases in Section 3**

R22 - Harmful if swallowed.

R41 - Risk of serious damage to eyes.

### **Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal responsibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.