

# SAFETY DATA SHEET NO. 10 PART No. PG202T

## 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT/TRADE NAME: CHAIN SPRAY 12x500ml

**SUPPLIER:** Autogem Motor Concepts LLP

Unit 6, Space Business Park

Abbey Road, Park Royal

London NW10 7SU

 TEL:
 00 44 (0) 208 838 0910

 FAX:
 00 44(0) 208 838 1854

 E-mail:
 sales@autogem.co.uk

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS % CAS No. EINECS NO.

OILS POWDERS TACKIFIERS

HYDROCARBON SOLVENTS 64742-49-0

HYDROCARBON PROPELLANT

## 3. HAZARDS IDENTIFICATION

RISK PHRASES: R11 HIGHLY FLAMMABLE

## 4. FIRST AID MEASURES

INHALATION: MOVE THE EXPOSED PERSON TO FRESH AIR. KEEP WARM AND AT REST. PERFORM ARTIFICIAL RESPIRATION IF

BREATHING HAS STOPPED. IF BREATHING IS DIFFICULT, GIVE OXYGEN. OBTAIN MEDICAL ATTENTION URGENTLY.

SKIN CONTACT: WASH SKIN WITH COPIOUS AMOUNTS OF WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. IF

IRRITATION PERSISTS, OBTAIN MEDICAL ATTENTION. WASH OR DRY CLEAN CLOTHING BEFORE RE-USE.

EYE CONTACT: WASH EYES WITH COPIOUS AMOUNTS OF WATER WHILE LIFTING THE EYELIDS. CONTINUE TO RINSE FOR AT LEAST 10

MINUTES. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

INGESTION: RINSE MOUTH THOROUGHLY. KEEP WARM AND AT REST. PERFORM ARTIFICIAL RESPIRATION IF BREATHING HAS

STOPPED. IF BREATHING BECOMES DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

## 5. FIRE-FIGHTING MEASURES.

SUITABLE EXTINGUISHING MEDIA: POWDER, CO2 OR ALCOHOL RESISTANT FOAM.

UNSUITABLE EXTINGUISHING MEDIA: DO NOT USE WATER JET.

SPECIAL EXPOSURE HAZARDS IN FIRE: RISK OF EXPLODING CANS.

REQUIRED SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS: SELF CONTAINED BREATHING APPARATUS IN ENCLOSED SPACES.

## 6. ACCIDENTAL RELEASE MEASURES.

PERSONAL PRECAUTIONS: EXTINGUISHING SOURCES OF IGNITION. AVOID SPARKS, FLAMES, HEAT AND SMOKING. PROVIDE

VENTILATION.

**ENVIRONMENTAL PRECAUTIONS:** DO NOT RUN OFF TO SEWER. IF THIS OCCURS INFORM AUTHORITIES.

METHODS FOR CLEANING: ABSORB IN INERT MATERIAL AND PLACE IN CONTAINERS.

## 7. HANDLING AND STORAGE

**HANDLING:** HANDLE WITH CARE.

**STORAGE:** STORE IN COOL, DRY PLACE OUT OF DIRECT SUNLIGHT AND BELOW 50°C. FOLLOW LOCAL

REGULATIONS.

## 8. EXPOSURE CONTROLS

**EXPOSURE LIMITS:** CALCULATIONS SHOW THE RECOMMENDED LONG TERM OCCUPATIONAL EXPOSURE LIMIT FOR THIS

PRODUCT IS TWA 8hr 1000mg/m<sup>3</sup>.

**RESPIRATORY PROTECTION:** PROVIDE ADEQUATE VENTILATION.

HAND PROTECTION: BUTYL RUBBER GLOVES.

**SKIN PROTECTION:** WEAR APPROPRIATE SKIN PROTECTION.

**EYE PROTECTION:** GOGGLES IF SPLASHING OF EYES POSSIBLE.

## 9. PHYSICAL AND CHEMICAL APPEARANCE PROPERTIES

APPEARANCE: BROWN LIQUID AUTO IGNITION TEMPERATURE: >200°C

**ODOUR:** MILD **EXPLOSION HAZARD:** EXPLODING CANS

Ph: N/A **OXIDISING PROPERTIES:** N/A **BOILING POINT:** N/A **VAPOUR PRESSURE:** N/A **MELTING POINT:** N/A SPECIFIC GRAVITY: 0.724-0.742 FLASH POINT: 1°C **SOLUBITILITY IN WATER:** INSOLUBLE.

FLAMMABILITY: HIGHLY FLAMMABLE

#### 10. STABILITY AND REACTIVITY

**STABILITY:** NORMALLY STABLE.

MATERIALS TO AVOID: STRONG OXIDISING AGENTS, ACIDS AND ALKALIS.

**CONDITIONS TO AVOID**: HEAT, SOURCES OF IGNITION.

**DECOMPOSITION PRODUCTS:** CO<sub>2</sub> AND CO.

# 11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA: LD 50 (ORAL RAT) ALCOHOL 4.7 – 5.8g/kg

LD 50 (ORAL RAT) ALIPHATIC > 10g/kg

**INHALATION:** VAPOUR CONCENTRATION ABOVE RECOMMENDED EXPOSURE LIMITS ARE IRRITATING TO THE EYES

AND RESPIRATORY TRACT. MAY CAUSE HEADHACHES DIZZINESS AND DROWSINESS.

**SKIN CONTACT:** LOW ORDER OF TOXICITY. FREAUENT/PROLONGED USE MAY IRRITATING AND CAUSE DERMATITIS.

**EYE CONTACT:** IRRITATING, BUT DOES NOT INJURE EYE TISSUE.

INGESTION: MINIMAL TOXICITY. SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM MAY

CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA.

## 12. ECOLOGICAL INFORMATION

**DEGRADABILITY:** PARTIALLY DEGRADABLE PRODUCT.

**ENVIRONMENTAL HAZARD:** PARTIALLY EVAPORATES.

#### 13. DISPOSAL CONSIDERATIONS

SAFE HANDLING: DISPOSE OF IN A SAFE AREA UNDER CONTROLLED CONDITIONS TO COMPLY WITH LOCAL AND

NATIONAL REGULATIONS.

#### 14. TRANSPORT INFORMATION

**UN NUMBER:** UN 1950 CLASS: 2.1 **PACKAGING GROUP:** N/A **HAZCHEM CODE:** N/A RID/ADR: 2.1 **IMO CLASS:** 2.1 TREMCARD NUMBER: CLASS 2 **CCT NUMBER:** NONE

## 15. REGULATION INFORMATION

CLASSIFICATION AND LABELLING ACCORDING TO EEC DIRECTIVES

**CLASSIFICATION:** F EXTREMELY FLAMMABLE.

RISK PHRASES: R11 HIGHLY FLAMMABLE

SAFETY PHRASES: S2 KEEP OUT OF REACH OF CHILDREN

S16 KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING.

S23 DO NOT BREATHE VAPOUR.

S46 IF SWALLOWED SEEK MEDICAL ADVICE IMMEDIATELY AND

HOW THIS CONTAINER.

CAUTION: PRESSURISED CONTAINER, PROTECT FROM SUNLIGHT. DO

NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT BURN EVEN AFTER USE. DO NOT SPRAY ONTO A NAKED

FLAME OR ANY INCANDESCENT MATERIAL.

**NOTE:** THIS DATA SHEET DOES NOT CONSTITUTE A USER'S ASSEMENT OF WORKPLACE RISK AS REQUIRED BY HSW ACT, COSHH, MANAGEMENT OF HEALTH AND SAFETY AT WORK REGULATIONS, OR OTHER HEALTH AND SAFETY LEGISLATION.

## 16. OTHER INFORMATION

**RECOMMENDED USES:** CHAIN SPRAY.

**SOURCES OF KEY DATA:** CHIP 2 AND CHIP 96/97.